

arman P-Series stoves are a true testament to engineering excellence and heating performance. These customizable units create a striking statement in your living space, blending clean lines and mechanical flair with the elegant design of your home. Multiple sizes allow for seamless integration into any room, while efficiently heating your space.

#### **Features**

- · Quiet, variable-speed blower
- · High efficiencies with accordion heat exchanger
- · Room temperature regulated to within one degree
- · Cleaner glass thanks to exclusive air wash system
- Easy to use with hidden, color control
- · Less loading with large hopper capacities
- · Less maintenance with large ash pan
- · Elegant flame-reactive mirrored glass
- Installation made easy with direct vent

### **Key Technologies**

ESP Temperature Control Harman pellet products



utilize an Exhaust Sensing Probe system (ESP) to deliver precise heat control. ESP constantly monitors and adjusts heat output to maintain set room temperatures within one degree.

PelletPro™ Technology This patented system makes it possible to burn any grade of pellet fuel with maximum heat and efficiency. A bottom-up feed system burns each pellet completely and allows for 24-hour heating.



# **Aesthetic Options**

Trim Kits - Include door trim, ash lip and ash door trim. Available in brushed stainless steel.



P43/P61 Leaf



P68 Leaf



P43/P61/P68 Modern



#### Side Heat Shields



Matte Black with Stainless Steel accent



Matte Black

#### Ash Door Inlays



Deer Slate



Trail Riders Slate



heat shields with brushed stainless accent and log set.

### Logs



Ceramic Log Kit

# **Utility Options**

Hopper Extension



55lb hopper extention (P43) 60lb hopper extention (P61 & P68)

Installation Solutions



Direct Vent Wall Pass-Through




Outside Air Termination Cap




Harman Protect Cast Iron Hearth Pad


# **Specifications**



# Clearance to Combustibles



P43: 10" with side shield: 16" w/o side shield P61 & P68: 14" with side shield; 20" w/o side shield Standard Installation



P43: 9" with or without side shield P61 & P68: 9" with side shield; I3" w/o side shield

Corner Installation

## P43 Pellet Stove



BTU/Hr Input<sup>1</sup>...... 17,200-43,500 Efficiency<sup>2</sup>...... 84% LHV; 77% HHV

Heating Capacity<sup>3</sup>..... 800-2,400 sq ft

Hopper Capacity...... 50 lb

105lbs with optional hopper extension

Fuel Type..... Pellet

Feed Rate................ 1.9-4.7lb/hr

Venting Size...... 3"

Weight...... 213 lb

Mobile Home Approved

### P61 Pellet Stove



BTU/Hr Input<sup>1</sup>...... 21,400-60,700

Efficiency<sup>2</sup>...... 85% LHV; 79% HHV

Emissions..... 1.5g/hr

Heating Capacity<sup>3</sup>..... 1,300-3,500 sq ft

Hopper Capacity...... 72 lb

132lbs with optional hopper extension

Fuel Type..... Pellet

Feed Rate...... 1.5-6.6lb/hr

Venting Size...... 3"

Weight...... 247 lb

Mobile Home Approved

### P68 Pellet Stove



BTU/Hr Input<sup>1</sup>...... 20,200-67,600

Efficiency<sup>2</sup>...... 85% LHV; 79% HHV

Emissions..... 1.4g/hr

Heating Capacity<sup>3</sup>..... 1,500-3,900 sq ft

Hopper Capacity...... 76 lb

136lbs with optional hopper extension

Fuel Type..... Pellet

Feed Rate...... 1.7-7.8lb/hr

Venting Size...... 3"

Weight...... 259 lb

Mobile Home Approved

### Floor Protection

Stove	P43	P61	P68
Standard Installation	25-7/16"× 26-3/4" minimum 25-7/16"× 33-3/16" if touching wall	25-1/8"x 27-3/4" minimum 25-1/8"x 34-3/16" if touching wall	25-3/16"× 27-3/4" minimum 25-3/16"× 54" if touching wall
Corner Installation	40"x 40" touching wall	40"x 40" touching wall	40"x 40" touching wall


# A Standard of Excellence

In 1979, Dane Harman used his welding skills and design talent to build his first wood stove, setting the stage for a journey full of entrepreneurial energy and innovation. Built to a Standard and Not a Price has remained an unwavering promise since that first model was constructed, and is exemplified today through Harman's multiple patents and industry awards. Harman heating solutions are built to withstand the test of time with reliable warmth and aesthetic elegance, staying true to Dane's dedication to optimal performance and engineering excellence.

#### YOUR HARMAN DEALER IS:



WWW.HARMANSTOVES.COM



HAR-1714U-0823

#### LIMITED LIFETIME WARRANTY<sup>4</sup>

The strongest in the industry, Harman provides a limited lifetime warranty on the most important aspects: firebox and heat exchanger.

EPA tested input 'Weighted Average LHV (Low Heating Value) Efficiency. HHV (High Heat Value) efficiency used to qualify products for Tax Credit beginning in 2021. 'See you local authorized Harman dealer for help in determining the product that best suits your heating needs based on climate and home efficiency. 'For full warranty details

oduct appearance, including flame, may differ from image. Product ons and pricing subject to change without notice. The images and ns in this brochure are provided to assist you in product selection (density and pellet shape may affect hopper capacity. But's may g on type of fuel used. Refer to installation manual for complete or

Appliance surfaces get extremely HOT and can cause severe burns if touched. Keep a safe distance away. To learn more visit www.harmanstoves.com/fireplacesafety